



# miniUCS Elastix<sup>®</sup> Appliance

full-featured Elastix Communication Server





The miniUCS, NLX series, lets you control all your business communications and stay in touch with your customers, suppliers or employees wherever they are.

## Features

- Auto Attendants
- Voicemail
- Dial-By-Name Directory
- Music on Hold
- Multiple Languages
- Ring Groups
- Call Queue
- Call Waiting
- Caller Display
- Conference Call
- Call Hold/Transfer
- Call Park
- Call Pickup
- Automatic Fax Detection
- Remote Management
- Remote Extensions and much more.

## Empower your business

With Elastix® miniUCS and our Elastix® software take your business to new levels of communication.

The telephony solution that your business needs, Elastix® integrates multiple software functionality and stable certified hardware guaranteeing the precise control of all your communications.

### Compact and Robust Design

The miniUCS features an attractive and robust metal housing design, simple and compact which makes it portable and easy to maintain.

### Low Power Consumption

With only 14W of nominal power consumption, the miniUCS offers significant savings in energy and operating costs, contributing to the conservation of the environment.

### Fits your needs

You can configure your server with up to 8 analog ports (FXO/FXS) or up to 4 digital ports, according to your needs.

### Remote Management

Thanks to the powerful pre-installed Elastix software, you will have all your business communications fluid and under control.

## Technical Specifications

Telephony	
Internal Analog Ports (FXO/FXS)	Configurable: Up to 8
Internal Digital Ports	Up to 1 E1/T1/J1 or 4 BRI
PCI Expansion Slots	1 PCIe **
Extensions (SIP/IAX)	Up to 50*
Concurrent Calls	Up to 32*
Operating System	Elastix 32 bits
Hardware	
CPU	1.1 GHz
RAM	1 GB DDR2
Hard Drive	16 GB (Compact Flash)
Network Interface	3 x Gigabit Ethernet
USB Ports	2 in rear panel
Operation Features	
Nominal Power	14 W
Operation Voltage	120/240v Auto switching
Physical Features	
Height	2.2" (56 mm)
Width	7.13" (181 mm)
Depth	6.42" (163 mm)
Weight	0.84 Kg (1.85 lb)

## Buy Now

For further information or sales, please contact us at:  
sales@elastix.com or 1-877-ELASTIX



© 2014 Elastix. All rights reserved.

\* Represents a safe estimate on a basic scenario. Visit <http://elx.ec/benchmark> for more details.  
\*\* Only a limited telephony card models supported. Visit <http://elx.ec/nlxcards> for more details.